



INTERMEDIATE PRESSURE LIMITS
 INTERMEDIATE PRESSURES MUST BE BETWEEN
 120-140 PSIG AT BOTH 300 AND 2,000 PSIG WITH A
 MAXIMUM OF 8 PSIG DIFFERENCE BETWEEN THE
 INTERMEDIATE PRESSURES TAKEN AT 300 AND
 2,000 PSIG. INTERMEDIATE PRESSURE
 CREEPAGE ALLOWED AFTER SEATING OF A NEW
 SEAT.

ITEM NO.	QTY. REQD.	PART NO.	DESCRIPTION	SUGG. RETAIL
1	1	10-101-113	YOKE SCREW, 7/16 THREAD	3.00
1	1	10-101-120	YOKE SCREW, 3/8 THREAD	3.50
1	1	10-101-122	YOKE SCREW, 5/16 THREAD	7.80
2	1	01-020-127	RETAINER, OSCILLATOR	6.00
3	1	01-020-127	O-RING (BLUE)	.40
4	1	01-020-128	SPRING	1.20
5	1	10-107-004	OSCILLATOR ASSEMBLY	13.00
6	1	01-020-128	O-RING (WHITE & BLACK)	1.00
7	1	01-020-128	O-RING (BLACK)	.80
8	1	10-101-110	1ST STAGE INLET PROTECTOR	2.50
9	1	01-020-128	O-RING (PURPLE)	.40
10	1	10-101-124	H.P. ADAPTER W/O-RING, HAS LG. MALE THD. & SM. FEMALE THD.	3.50
11	1	10-101-124	H.P. ADAPTER W/O-RING, HAS LG. MALE THD. & SM. FEMALE THD.	3.50
12	1	10-101-134	H.P. ADAPTER W/O-RING, HAS SM. MALE THD. & LG. FEMALE THD.	3.50
13	1	01-020-135	O-RING (BLUE)	.40
14	1	10-101-022	H.P. ADAPTER W/O-RING, HAS SM. MALE THD. & LG. FEMALE THD.	3.50
15	1	10-101-134	PLUG, 7/16-20 H.P.	1.20
16	1	10-101-039	PLUG, W/O-RING, 7/16-20 H.P.	1.40
17	1	10-101-126	SEAT RETAINER	5.00
18	1	01-020-137	O-RING (RED)	.40
19	1	10-101-126	SEAT	2.50
20	1	01-020-137	O-RING (PURPLE)	.40
21	1	01-020-113	DECAL	1.00
22	1	01-020-120	DECAL, WARNING	1.50
23	1	10-107-002	BODY & YOKE SCREW SET, 5/16 THREAD	155.00
24	2	01-020-134	O-RING (BLUE)	.40
25	1	10-107-107	SPRING PAD	1.50
26	1	01-020-107	SPRING	3.40
27	1	10-107-008	STEM	2.50
28	1	01-020-108	RETAINER, STEM	2.00
29	1	01-020-138	O-RING (GRAY)	.40
30	3	21-000-101	WASHER	.45
31	1	10-107-007	SPRING	4.25
32	1	10-107-003	PISTON	10.00
33	1	01-020-144	O-RING (RED)	.40
34	1	10-107-103	RETAINER, PISTON	7.00
35	1	01-020-132	O-RING (BLUE)	.40
36	1	10-101-104	PLUG	1.20
37	1	10-101-006	PLUG W/O-RING	1.20
38	1	01-020-101	RETAINER	.45
39	1	01-020-144	FILLET	.40
40	1	01-020-111	O-RING (BLUE)	.40
41	1	10-101-111	ADAPTER, FRENCH	3.00
42	1	01-020-109	PLUG, CONICAL	.80
43	1	41-008-000	SILICONE GREASE, 7 GIL	2.00
44	1	41-010-107	REPAIR PROCEDURES	N/C
45	1	42-101-187	MANUAL	2.00

PRICES SUBJECT TO CHANGE WITHOUT NOTICE.

NOTES:

- NOT SHOWN
- △ OPTIONAL ITEM
- △ OLDER CONFIGURATION
- △ FOR OLDER CONFIGURATION H.P. HOSES USED W/NEW CONFIGURATION REGULATORS
- △ NOT COVERED UNDER WARRANTY
- △ MAXIMUM 3 WASHERS P/N 01-020-103 WASHERS ARE USED AS SHIMS TO ADJUST THE INTERMEDIATE PRESSURE TO BE WITHIN THE SPECIFIED LIMITS.
- ⊕ ANNUAL REPLACEMENT
- ◇ DYNAMIC O-RING REPLACE ANNUALLY
- ◁ TORQUE IN INCH POUNDS

MARK VII FIRST STAGE REGULATOR

N	MAY '84	CONFIGURATION 8
REV.	DATE	

SCUBAPRO®

CAT. NO. 10-107-000